

Report ID: 348842
Date of sample receipt: 16/05/23
Date of issue: 19/06/23

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Sample name: sgabello LORIA telaio metallo

SAMPLE N° 348842


Overall dimensions: 570 x 500 x 980 (h) mm

List of test reports:

1. Stability test ANSI-BIFMA X5.4-2020/21
2. Unit drop test - dynamic ANSI-BIFMA X5.4-2020/17
3. Footrest Static Load test - Vertical ANSI-BIFMA X5.4-2020/27
4. Footrest durability test ANSI-BIFMA X5.4-2020/28
5. Backrest durability test - horizontal - cyclic ANSI-BIFMA X5.4-2020/7
6. Seating durability test - cyclic ANSI-BIFMA X5.4-2020/14
7. Backrest strength test - horizontal - static ANSI-BIFMA X5.4-2020/5
8. Drop test - dynamic ANSI-BIFMA X5.4-2020/15
9. Leg strength test - front and side application ANSI-BIFMA X5.4-2020/16
10. Arm strength test - horizontal - static ANSI-BIFMA X5.4-2020/9
11. Arm durability test for single seat units - angular - cyclic ANSI-BIFMA-X5.4-2020/13



This document is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli


The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

SAMPLE N° 348842

Date of issue: 19/06/23
Sample weight: Not determined
Sample name: sgabello LORIA telaio metallo



Side view



Rear view



Bottom view

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 1

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 18/05/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Stability test ANSI-BIFMA X5.4-2020/21

Clause 21.3

Rear stability for non-tilting units

Seat load:	60 kg	
Minimum force required:	93 N	
Measured force:	> 120 N *	Does not overturn

Clause 21.4

Rear stability for tilting units

Loading discs on the seat	/
---------------------------	---

Clause 21.5

Front Stability for Units Less than 36.3 kg

Seat load:	600 N	
Minimum force required:	20 N	
Measured force:	> 20 N	Does not overturn

Clause 21.6

Front Stability for Units Greater Than or Equal to 36.3 kg

Weight of the unit:	7 kg
Minimum force required:	/ N
Measured force:	/ N

The test results comply with the requirements in clause 21.3.3 and 21.5.4 of ANSI-BIFMA X5.4-2020.

* Unless otherwise specified, measurement uncertainty expanded to a confidence level of about 95% is $\pm 5\%$.

The measurement uncertainties stated in this document have been determined according to UNI CEI 70098-3:2016.

They were estimated as expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor k corresponding to a confidence level of about 95%. Normally k=2.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 2

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 18/05/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Unit drop test - dynamic ANSI-BIFMA X5.4-2020/17

Weight of the unit: 7 kg

Test results:

Drop height mm	Number of drops per side	Remarks
180	1	No defects

The test results comply with the requirements in clause 17.5 of ANSI-BIFMA X5.4-2020.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 3

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 18/05/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Footrest Static Load test - Vertical ANSI-BIFMA X5.4-2020/27

Type of foot rest: fixed

Test results:

Functional load

Force on footrest F1 N	Number of cycles	Time of application	Remarks
445	1	1 m	No defects
890	1	1 m	No defects

Proof load

Force on footrest N	Number of cycles	Time of application	Remarks
1.334	1	10 s	No defects

The test results comply with the requirements in clause 27.4.2 and 27.5 of ANSI-BIFMA X5.4-2020.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 4

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 18/05/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Footrest durability test ANSI-BIFMA X5.4-2020/28

Test results:

Load on footrest N	Number of cycles	Remarks
890	50.000	No defects

The test results comply with the requirements in clause 28.5 of ANSI-BIFMA X5.4-2020.

Unless otherwise specified, measurement uncertainty expanded to a confidence level of about 95% is ± 5 N.

The measurement uncertainties stated in this document have been determined according to UNI CEI 70098-3:2016.

They were estimated as expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor k corresponding to a confidence level of about 95%. Normally k=2.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 5

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 22/05/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Backrest durability test - horizontal - cyclic ANSI-BIFMA X5.4-2020/7

Backrest height: < 452 mm

Test results:

Horizontal force N	Number of cycles per position	Remarks
334	120.000	No defects

The test results comply with the requirements in clause 7.5 of ANSI-BIFMA X5.4-2020.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 6

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 30/05/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Seating durability test - cyclic ANSI-BIFMA X5.4-2020/14

Height of drop: 36 mm above the uncompressed seat surface

Test results:

Mass of drop kg	Number of drops	Remarks
57	100.000	No defects

The test results comply with the requirements in clause 14.5 of ANSI-BIFMA X5.4-2020.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 7

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 08/06/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Backrest strength test - horizontal - static ANSI-BIFMA X5.4-2020/5

Backrest height: < 452 mm

Test results:

Back load for each seating position N	Time of application	Remarks
667	1 m	No defects
1.112	10 s	No defects

The test results comply with the requirements in clause 5.5 of ANSI-BIFMA X5.4-2020.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 8

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 08/06/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Drop test - dynamic ANSI-BIFMA X5.4-2020/15

Test results:

Bag weight kg	Drop height mm	Number of cycles per position	Remarks
102	152	1	No defects
136	152	1	No defects

The test results comply with the requirements in clause 15.5 of ANSI-BIFMA X5.4-2020.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 9

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 08/06/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Leg strength test - front and side application ANSI-BIFMA X5.4-2020/16

Weight of the unit: 7 kg

Test results:

Front load test:

Horizontal force N	Time of application	Leg tested	Remarks
334	1 m	left	No defects
334	1 m	right	No defects
503	10 s	left	No defects
503	10 s	right	No defects

Side load test:

Horizontal force N	Time of application	Leg tested	Remarks
334	1 m	front	No defects
334	1 m	rear	No defects
503	10 s	front	No defects
503	10 s	rear	No defects

The test results comply with the requirements in clause 16.5 of ANSI-BIFMA X5.4-2020.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 10

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 09/06/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Arm strength test - horizontal - static ANSI-BIFMA X5.4-2020/9

Distance between the armrests: 555 mm

Test results:

Load on arm rest N	Time of application	Direction of load application	Remarks
445	1 m	inwards	No defects
445	1 m	outwards	No defects
667	10 s	inwards	No defects
667	10 s	outwards	No defects

The test results comply with the requirements in clause 9.5 of ANSI-BIFMA X5.4-2020.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

348842 / 11

Revision: 0
Date of sample receipt: 16/05/23
Date of test: 14/06/23
Date of issue: 19/06/23



Sample name: sgabello LORIA telaio metallo

CERANTOLA S.P.A.
VIA GIORGIONE 2-ZONA IND.LE
31037 RAMON DI LORIA (TV)
ITALIA

Arm durability test for single seat units - angular - cyclic ANSI-BIFMA-X5.4-2020/13

Test results:

Vertical load N	Number of cycles	Remarks
400	60.000	No defects

The test results comply with the requirements in clause 13.5 of ANSI-BIFMA X5.4-2020.

This test report is part of a PDF file digitally signed by Paolo Tirelli.

The deputy director
Dr. Paolo Tirelli

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.